High-voltage Switching Transistor (–400V, –2A)

2SA1862

Features

- 1) High breakdown voltage. (BVcEo = -400V)
- 2) Low saturation voltage.

(Max. Vce (sat) = -0.5V at Ic / IB = -500mA/-100mA)


- 3) High switching speed, typically tf = $0.4\mu s$ at Ic = -1A.
- 4) Wide SOA (safe operating area).

● Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit	
Collector-base voltage	Vсво	-400	V	
Collector-emitter voltage	Vceo	-400	V	
Emitter-base voltage	VEBO	-7	V	
Collector current	lc	-2	A (DC)	
	IC IC	-4	A (Pulse) *	
Collector power dissipation	Pc	1	W	
	PC	10	W (Tc=25°C)	
Junction temperature	Tj	150	°C	
Storage temperature	Tstg	-55 to +150	°C	

^{*} Single pulse, Pw=10ms

●External dimensions (Unit: mm)




●Packaging specifications and hFE


Туре	2SA1862
Package	CPT3
hfe	Р
Code	TL
Basic ordering unit (pieces)	2500

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Тур.	Max.	Unit	Conditions
Collector-base breakdown voltage	ВУсво	-400	-	-	V	Ic= -50μA
Collector-emitter breakdown voltage	BVceo	-400	-	-	V	Ic=-1mA
Emitter-base breakdown voltage	ВVево	-7	-	-	V	I _E = -50μA
Collector cutoff current	Ісво	-	-	-10	μΑ	Vcb= -400V
Emitter cutoff current	ІЕВО	-	-	-10	μΑ	V _{EB} = -5V
Collector-emitter saturation voltage	VcE(sat)	-	-	-0.5	V	Ic/I _B = -0.5A/ -0.1A
Base-emitter saturation voltage	V _{BE(sat)}	-	-	-1.2	V	Ic/I _B = -0.5A/ -0.1A
DC current transfer ratio	hre	82	-	180	-	Vce= -5V, Ic= -0.1A
Transition frequency	f⊤	-	18	-	MHz	Vcb= -10V, IE=0.1A, f=5MHz
Output capacitance	Cob	-	30	-	pF	Vce=-10V, Ie=0A, f=1MHz
Turn-on time	ton	-	0.2	-	μs	Ic=-1A, R _L =150Ω
Storage time	tstg	-	1.8	-	μs	I _{B1} =-I _{B2} = -0.2A
Fall time	tf	-	0.4	-	μs	Vcc ≃ -150V

•Electrical characteristic curves








Fig.2 Grounded emitter propagation characteristics




Fig.3 DC current gain vs. collector current




Fig.4 Collector-emitter saturation voltage vs. collector current
Base-emitter saturation voltage vs. collector current




Fig.5 Gain bandwidth product vs. emitter current




Fig.6 Collector output capacitance vs. collector-bass voltage Emitter input capacitance vs. emitter-base voltage




Fig.7 Safe operating area




Fig.8 Transient thermal resistance

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any
 means without prior permission of ROHM CO..LTD.
- The contents described herein are subject to change without notice. The specifications for the
 product described in this document are for reference only. Upon actual use, therefore, please request
 that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or
 otherwise dispose of the same, no express or implied right or license to practice or commercially
 exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.

