

JVC

SERVICE MANUAL

LCD TELEVISION

LT-19A200/AK



HDTV
HIGH DEFINITION TELEVISION

HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE

DOLBY
DIGITAL

ENERGY STAR

There may be multiple versions of this TV model.

The TV version is identified by the letters next to the model number on the TV's Rating.

(See illustration).

Use the service manual that matches the version of the TV.




TABLE OF CONTENTS

1 PRECAUTION	1-3
2 SPECIFIC SERVICE INSTRUCTIONS	1-4
3 DISASSEMBLY	1-7
4 ADJUSTMENT	1-10
5 TROUBLESHOOTING	1-13

WITH SOLDERING IRON:

- (1) Using desoldering braid, remove the solder from all pins of the flat pack-IC. When you use solder flux which is applied to all pins of the flat pack-IC, you can remove it easily. (Fig.2-3)




Fig.2-3

- (2) Lift each lead of the flat pack-IC upward one by one, using a sharp pin or wire to which solder will not adhere (iron wire). When heating the pins, use a fine tip soldering iron or a hot air desoldering machine. (Fig.2-4)




Fig.2-4

- (3) Bottom of the flat pack-IC is fixed with glue to the PWB; when removing entire flat pack-IC, first apply soldering iron to center of the flat pack-IC and heat up. Then remove (glue will be melted). (Fig.2-6)
- (4) Release the flat pack-IC from the PWB using tweezers. (Fig.2-6)

WITH IRON WIRE:

- (1) Using desoldering braid, remove the solder from all pins of the flat pack-IC. When you use solder flux which is applied to all pins of the flat pack-IC, you can remove it easily. (Fig.2-3)
- (2) Affix the wire to a workbench or solid mounting point, as shown in Fig.2-5.
- (3) While heating the pins using a fine tip soldering iron or hot air blower, pull up the wire as the solder melts so as to lift the IC leads from the PWB contact pads as shown in Fig.2-5.
- (4) Bottom of the flat pack-IC is fixed with glue to the PWB; when removing entire flat pack-IC, first apply soldering iron to center of the flat pack-IC and heat up. Then remove (glue will be melted). (Fig.2-6)
- (5) Release the flat pack-IC from the PWB using tweezers. (Fig.2-6)

NOTE:

When using a soldering iron, care must be taken to ensure that the flat pack-IC is not being held by glue. When the flat pack-IC is removed from the PWB, handle it gently because it may be damaged if force is applied.




Fig.2-5




Fig.2-6

2.1.3.2 INSTALLATION

- (1) Using desoldering braid, remove the solder from the foil of each pin of the flat pack-IC on the PWB so you can install a replacement flat pack-IC more easily.
- (2) The ● mark on the flat pack-IC indicates pin 1. (See Fig.2-7.) Be sure this mark matches the pin 1 on the PCB when positioning for installation. Then presolder the four corners of the flat pack-IC. (See Fig.2-8.)
- (3) Solder all pins of the flat pack-IC. Be sure that none of the pins have solder bridges.




Fig.2-7




Fig.2-8

2.1.4 INSTRUCTIONS FOR HANDLING SEMI-CONDUCTORS

Electrostatic breakdown of the semi-conductors may occur due to a potential difference caused by electrostatic charge during unpacking or repair work.


2.1.4.1 Ground for Human Body

Be sure to wear a grounding band ($1M\Omega$) that is properly grounded to remove any static electricity that may be charged on the body.


2.1.4.2 Ground for Workbench

Be sure to place a conductive sheet or copper plate with proper grounding ($1M\Omega$) on the workbench or other surface, where the semi-conductors are to be placed. Because the static electricity charge on clothing will not escape through the body grounding band, be careful to avoid contacting semi-conductors with your clothing.

<Incorrect>



<Correct>






Fig. D1





Fig. D2

SECTION 5


TROUBLESHOOTING

5.1 Power Supply Section


FLOW CHART NO.1




FLOW CHART NO.2




FLOW CHART NO.3











FLOW CHART NO.4





FLOW CHART NO.5




FLOW CHART NO.6**FLOW CHART NO.7****FLOW CHART NO.8****FLOW CHART NO.9**

FLOW CHART NO.10**FLOW CHART NO.11****FLOW CHART NO.12****FLOW CHART NO.13**


FLOW CHART NO.14**FLOW CHART NO.15**

5.2 Video Signal Section


FLOW CHART NO.1






FLOW CHART NO.2




FLOW CHART NO.3




FLOW CHART NO.4**FLOW CHART NO.5****FLOW CHART NO.6**



5.3 Audio Signal Section


FLOW CHART NO.1



FLOW CHART NO.2



FLOW CHART NO.3**FLOW CHART NO.4**

FLOW CHART NO.5



Victor Company of Japan, Limited

Display Division 12, 3-chome, Moriya-cho, Kanagawa-ku, Yokohama-city, Kanagawa-prefecture, 221-8528, Japan

(No.YA713<Rev.002>)

Printed in Japan
VSE

CONTENTS

USING P.W. BOARD & REMOTE CONTROL UNIT	3-2
EXPLODED VIEW PARTS LIST	3-3
EXPLODED VIEW	3-4
PRINTED WIRING BOARD PARTS LIST	3-6
MAIN P.W. BOARD ASS'Y (FU-1ESA21426)	3-6
JACK P.W. BOARD ASS'Y (FU-1ESA20966-1)	3-9
FUNCTION P.W. BOARD ASS'Y (FU-1ESA20966-2)	3-9
JUNCTION-A P.W. BOARD ASS'Y (FU-1ESA20966-3)	3-10
JUNCTION-B P.W. BOARD ASS'Y (FU-1ESA20966-4)	3-10
JUNCTION-C P.W. BOARD ASS'Y (FU-1ESA20966-5)	3-10
PACKING	3-11
PACKING PARTS LIST	3-12


USING P.W. BOARD & REMOTE CONTROL UNIT

P.W.B ASS'Y name	P.W.B ASS'Y No.
	LT-19A200/AK
MAIN P.W.B	FU-1ESA21426
JACK P.W.B	FU-1ESA20966-1
FUNCTION P.W.B	FU-1ESA20966-2
JUNCTION-A P.W.B	FU-1ESA20966-3
JUNCTION-B P.W.B	FU-1ESA20966-4
JUNCTION-C P.W.B	FU-1ESA20966-5
DIGITAL MAIN PWB UNIT	FU-1ESA19749 (Not supply individual parts of this PWB.)


EXPLODED VIEW PARTS LIST

Ref.No.	Part No.	Part Name	Description	Local
A 1	FU-1EM123673	FRONT CABINET		
A 3	FU-1EM325762	CONTROL PLATE		
A 4	FU-1EM023687	REAR CABINET		
A 5	FU-1EM223303	DECORATION PLATE		
A 7	FU-1ESA20168	STAND ASSEMBLY		
A 8	FU-1EM428257	JACK LABEL		
A 9	FU-1EM222783	JACK HOLDER(A)		
A 10	FU-1EM222784	JACK HOLDER(D)		
A 14	-----	POP LABEL		
B 1	FU-1EM222764	SHIELD BOX		
B 2	FU-1EM325619	STAND HOLDER		
B 3	FU-1EM323797	WALL MOUNT BRACKET	(x4)	
B 4	FU-1EM326198	PCB STUD		
B 7	FU-1EM425861	GASKET	(x4)	
B 8	FU-1EM325677	SPEAKER HOLDER	(x2)	
WR 1	FU-WX1A94N0-105	WIRE ASSEMBLY		
WR 2	FU-WX1A94F0-101	WIRE ASSEMBLY		
WR 4	FU-WX1A94F0-101	WIRE ASSEMBLY		
WR 5	FU-WX1A94F0-111	WIRE ASSEMBLY		
WR 6	FU-WX1A94N0-106	WIRE ASSEMBLY		
L 1	FU-GBHP3100	SCREW	(x13)	
L 2	FU-GBJP3080	SCREW	(x4)	
L 3	FU-GBJS3060	SCREW	(x18)	
L 4	FU-GBHS3080	SCREW	(x4)	
L 8	FU-1EM420633A	ASSEMBLED SCREW	(x4)	
L 9	FU-FPH34100	SCREW	M4x10(x4)	
L 11	FU-1EM422042	HEX SCREW	(x2)	
L 12	FU-1EM424392A	ASSEMBLED SCREW	(x4)	
L 17	FU-1ESA19876	STAND SCREW KIT	Inc.POLY BAG(x3)	
LCD1	FU-UH19MXA	LCD MODULE		
SP1	FU-DS08070XQ001	SPEAKER		
SP2	FU-DS08070XQ001	SPEAKER		
△ PB 1	FU-1ESA21426	MAIN PWB		
△ PB 2	FU-1ESA20966-1	JACK PWB		
△ PB 3	FU-1ESA20966-2	FUNCTION PWB		
△ PB 4	FU-1ESA20966-3	JUNCTION-A PWB		
△ PB 5	FU-1ESA20966-4	JUNCTION-B PWB		
△ PB 6	FU-1ESA20966-5	JUNCTION-C PWB		
△ PB 7	FU-1ESA19749	DIGITAL MAIN PWB UNIT		

EXPLODED VIEW



See Electrical Parts List
for parts with this mark.



△Ref No.	Part No.	Part Name	Description	Local
SW107	FU-SST0101AL049	TACT SWITCH	CH-	
SW108	FU-SST0101AL049	TACT SWITCH	CH+	
SW109	FU-SST0101AL049	TACT SWITCH	POWER	

JUNCTION-A P.W. BOARD ASS'Y (FU-1ESA20966-3)

△Ref No.	Part No.	Part Name	Description	Local
CL101	FU-WX1A94N0-001	WIRE ASSY		
CN101	FU-JCTUB08TG002	CONNECTOR		


JUNCTION-B P.W. BOARD ASS'Y (FU-1ESA20966-4)

△Ref No.	Part No.	Part Name	Description	Local
CL862	FU-WX1A94N0-002	WIRE ASSY		
CN862B	FU-JCTUB04TG002	CONNECTOR		

JUNCTION-C P.W. BOARD ASS'Y (FU-1ESA20966-5)

△Ref No.	Part No.	Part Name	Description	Local
CL861	FU-WX1A94N0-002	WIRE ASSY		
CN861B	FU-JCTUB04TG002	CONNECTOR		

PACKING



PACKING PARTS LIST

△	Ref.No.	Part No.	Part Name	Description	Local
S	1	FU-1EM429197	PACKING CASE		
S	2	FU-1EM023885	CUSHION TOP		
S	3	FU-1EM023886	CUSHION BOTTOM	2pcs in 1set	
S	4	FU-1EM323958	SET BAG		
S	6	FU-1EM425888	STAND BAG		
X	1	FU-0EM408420A	POLY BAG		
△	X 2	FU-1EMN24940	INST BOOK	French/Spanish/English	
X	3	FU-NF900UD	REMOTE CONTROL		
X	4	FU-XB0M451MS002	DRY BATTERY	R6P/AA	
X 10		FU-1EMN24179	REGISTRATION CARD		
X 14		FU-1EMN24899	WARRANTY CARD		

JVC

SCHEMATIC DIAGRAMS

LCD TELEVISION

LT-19A200/AK

DVD-ROM No.SML2009Q1



HDTV
HIGH DEFINITION TELEVISION

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

**DOLBY®
DIGITAL**


 ENERGY STAR

There may be multiple versions of this TV model.

The TV version is identified by the letters next to the model number on the TV's Rating.

(See illustration).

Use the service manual that matches the version of the TV.



LT-19A200/AK

STANDARD CIRCUIT DIAGRAM

■ NOTE ON USING CIRCUIT DIAGRAMS

1.SAFETY

The components identified by the \triangle symbol and shading are critical for safety. For continued safety replace safety critical components only with manufacturer's recommended parts.

2.SPECIFIED VOLTAGE AND WAVEFORM VALUES

The voltage and waveform values have been measured under the following conditions.

- (1) Input signal : Colour bar signal
- (2) Setting positions of each knob/button and variable resistor : Original setting position when shipped
- (3) Internal resistance of tester : DC 20k Ω /V
- (4) Oscilloscope sweeping time : H \Rightarrow 20 μ s / div
: V \Rightarrow 5ms / div
: Others \Rightarrow Sweeping time is specified
- (5) Voltage values : All DC voltage values

* Since the voltage values of signal circuit vary to some extent according to adjustments, use them as reference values.

3. INDICATION OF PARTS SYMBOL [EXAMPLE]

- In the PW board : R1209 \rightarrow R209

4. INDICATIONS ON THE CIRCUIT DIAGRAM

(1) Resistors

- Resistance value

- No unit : [Ω]
- K : [k Ω]
- M : [M Ω]

- Rated allowable power

- No indication : 1/16 [W]
- Others : As specified

- Type

- No indication : Carbon resistor
- OMR : Oxide metal film resistor
- MFR : Metal film resistor
- MPR : Metal plate resistor
- UNFR : Uninflammable resistor
- FR : Fusible resistor

* Composition resistor 1/2 [W] is specified as 1/2S or Comp.

(2) Capacitors

- Capacitance value

- 1 or higher : [pF]
- less than 1 : [μ F]

(3) Withstand voltage

- No indication : DC50[V]
- Others : DC withstand voltage [V]
- AC indicated : AC withstand voltage [V]

* Electrolytic Capacitors

47/50[Example]: Capacitance value [μ F]/withstand voltage[V]

● Type

- | | |
|---------------|--------------------------------------|
| No indication | : Ceramic capacitor |
| MM | : Metallized mylar capacitor |
| PP | : Polypropylene capacitor |
| MPP | : Metallized polypropylene capacitor |
| MF | : Metallized film capacitor |
| TF | : Thin film capacitor |
| BP | : Bipolar electrolytic capacitor |
| TAN | : Tantalum capacitor |

(3) Coils

- No unit : [μ H]
- Others : As specified

(4) Power Supply




* Respective voltage values are indicated

(5) Test point



(6) Connecting method



(7) Ground symbol

- \perp : LIVE side ground
- $\not\perp$: ISOLATED(NEUTRAL) side ground
- \equiv : EARTH ground
- \Downarrow : DIGITAL ground

5. NOTE FOR REPAIRING SERVICE

This model's power circuit is partly different in the GND. The difference of the GND is shown by the LIVE : (\perp) side GND and the ISOLATED(NEUTRAL) : ($\not\perp$) side GND. Therefore, care must be taken for the following points.

- (1) Do not touch the LIVE side GND or the LIVE side GND and the ISOLATED(NEUTRAL) side GND simultaneously. If the above caution is not respected, an electric shock may be caused. Therefore, make sure that the power cord is surely removed from the receptacle when, for example, the chassis is pulled out.
- (2) Do not short between the LIVE side GND and ISOLATED(NEUTRAL) side GND or never measure with a measuring apparatus measure with a measuring apparatus (oscilloscope, etc.) the LIVE side GND and ISOLATED(NEUTRAL) side GND at the same time. If the above precaution is not respected, a fuse or any parts will be broken.

◆ Since the circuit diagram is a standard one, the circuit and circuit constants may be subject to change for improvement without any notice.

NOTE

- ◆ Due improvement in performance, some part numbers show in the circuit diagram may not agree with those indicated in the part list.
When ordering parts, please use the numbers that appear in the Parts List.

CONTENTS


SEMICONDUCTOR SHAPES	2-3
WIRING DIAGRAM [TV CABLE]	2-4
WIRING DIAGRAM	2-5
POWER SUPPLY BLOCK DIAGRAM	2-7
INVERTER BLOCK DIAGRAM	2-9
DIGITAL SIGNAL PROCESS BLOCK DIAGRAM	2-11
AUDIO BLOCK DIAGRAM	2-13
VIDEO BLOCK DIAGRAM	2-15
SYSTEM CONTROL BLOCK DIAGRAM	2-17
CIRCUIT DIAGRAMS	2-19
MAIN PWB CIRCUIT DIAGRAM	2-19
MAIN PWB CIRCUIT DIAGRAM (3/4) AND JUNCTION-B CIRCUIT DIAGRAM	2-23
FUNCTION PWB CIRCUIT DIAGRAM AND JUNCTION-A PWB CIRCUIT DIAGRAM	2-27
JACK AND JUNCTION-C PWB CIRCUIT DIAGRAM	2-29
DIGITAL MAIN PWB CIRCUIT DIAGRAM	2-31
PATTERN DIAGRAMS	2-41
MAIN PWB PATTERN	2-41
JACK PWB PATTERN	2-45
FUNCTION PWB PATTERN	2-46
JUNCTION-A PWB PATTERN	2-46
JUNCTION-B PWB PATTERN	2-46
JUNCTION-C PWB PATTERN	2-46
WAVEFORMS	2-47

USING P.W. BOARD


P.W.B ASS'Y name	LT-19A200/AK
MAIN P.W. BOARD	FU-1ESA21426
JACK P.W. BOARD	FU-1ESA20966-1
FUNCTION P.W. BOARD	FU-1ESA20966-2
JUNCTION-A P.W. BOARD	FU-1ESA20966-3
JUNCTION-B P.W. BOARD	FU-1ESA20966-4
JUNCTION-C P.W. BOARD	FU-1ESA20966-5
DIGITAL MAIN P.W. BOARD UNIT	FU-1ESA19749 (Not supply individual parts of this PWB.)

SEMICONDUCTOR SHAPES


TRANSISTOR




IC




CHIP IC



WIRING DIAGRAM [TV CABLE]




WIRING DIAGRAM



POWER SUPPLY BLOCK DIAGRAM

CAUTION !

Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit.
If Main Fuse (F601) is blown , check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply.
Otherwise it may cause some components in the power supply circuit to fail.




CAUTION ! : For continued protection against risk of fire,
replace only with same type 4 A, 125V fuse.


ATTENTION : Utiliser un fusible de rechange de même type de 4A, 125V.

NOTE:

The voltage for parts in hot circuit is measured using hot GND as a common terminal.




INVERTER BLOCK DIAGRAM




MAIN PWB

LCD PANEL
UNIT


DIGITAL SIGNAL PROCESS BLOCK DIAGRAM




AUDIO BLOCK DIAGRAM



VIDEO BLOCK DIAGRAM




SYSTEM CONTROL BLOCK DIAGRAM




CIRCUIT DIAGRAMS


MAIN PWB CIRCUIT DIAGRAM (1/4)



MAIN PWB CIRCUIT DIAGRAM (2/4)




MAIN PWB CIRCUIT DIAGRAM (3/4) AND JUNCTION-B CIRCUIT DIAGRAM



MAIN PWB CIRCUIT DIAGRAM (4/4)

CAUTION !


Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit.
If Main Fuse (F601) is blown , check to see that all components in the power supply
circuit are not defective before you connect the AC plug to the AC power supply.
Otherwise it may cause some components in the power supply circuit to fail.




CAUTION ! : For continued protection against risk of fire,
replace only with same type 4 A, 125V fuse.

NOTE:

The voltage for parts in hot circuit is measured using
hot GND as a common terminal.






FUNCTION PWB ASS'Y
FU-1ESA20966-2

JUNCTION-A PWB ASS'Y
FU-1ESA20966-3

JACK AND JUNCTION-C PWB CIRCUIT DIAGRAM



DIGITAL MAIN PWB CIRCUIT DIAGRAM (1/5)

*1 NOTE:


The order of pins shown in this diagram is different from that of actual IC3301.

IC3301 is divided into five and shown as IC3301 (1/5) ~ IC3301 (5/5) in this Digital Main Schematic Diagram Section.

This schematic is only for reference.

Avoid replacing individual parts.

Replace the entire PWB ASS'Y only.




DIGITAL MAIN PWB CIRCUIT DIAGRAM (2/5)

*1 NOTE:

The order of pins shown in this diagram is different from that of actual IC3301.

IC3301 is divided into five and shown as IC3301 (1/5) ~ IC3301 (5/5) in this Digital Main Schematic Diagram Section.

This schematic is only for reference.
Avoid replacing individual parts.
Replace the entire PWB ASS'Y only.




**DIGITAL MAIN PWB ASS'Y(2/5)
FU-1ESA19749**

DIGITAL MAIN PWB CIRCUIT DIAGRAM (3/5)

*1 NOTE:

The order of pins shown in this diagram is different from that of actual IC3301.
IC3301 is divided into five and shown as IC3301 (1/5) ~ IC3301 (5/5) in this Digital Main Schematic Diagram Section.

This schematic is only for reference.
Avoid replacing individual parts.
Replace the entire PWB ASS'Y only.




DIGITAL MAIN PWB CIRCUIT DIAGRAM (4/5)

*1 NOTE:

The order of pins shown in this diagram is different from that of actual IC3301.

IC3301 is divided into five and shown as IC3301 (1/5) ~ IC3301 (5/5) in this Digital Main Schematic Diagram Section.

This schematic is only for reference.
Avoid replacing individual parts.
Replace the entire PWB ASS'Y only.



**DIGITAL MAIN PWB ASS'Y(4/5)
FU-1ESA19749**

DIGITAL MAIN PWB CIRCUIT DIAGRAM (5/5)


*1 NOTE:

The order of pins shown in this diagram is different from that of actual IC3301.

IC3301 is divided into five and shown as IC3301 (1/5) ~ IC3301 (5/5) in this Digital Main Schematic Diagram Section.

This schematic is only for reference.
Avoid replacing individual parts.
Relpace the entire PWB ASS'Y only.


AUDIO SIGNAL




PATTERN DIAGRAMS

MAIN PWB PATTERN [SOLDER SIDE]


TOP
↑




MAIN PWB PATTERN [PARTS SIDE]




JACK PWB PATTERN [SOLDER SIDE]




JACK PWB PATTERN [PARTS SIDE]




FUNCTION PWB PATTERN [SOLDER SIDE]




FUNCTION PWB PATTERN [PARTS SIDE]




JUNCTION-A PWB PATTERN
[SOLDER SIDE]




JUNCTION-A PWB PATTERN
[PARTS SIDE]




JUNCTION-B PWB PATTERN
[SOLDER SIDE]




JUNCTION-B PWB PATTERN
[PARTS SIDE]



JUNCTION-C PWB PATTERN
[SOLDER SIDE]



JUNCTION-C PWB PATTERN
[PARTS SIDE]




WAVEFORMS


WF1 ~ WF7 = Waveforms to be observed at
Waveform check points.
(Shown in Schematic Diagram.)

Input: NTSC Color Bar Signal (with 1kHz Audio Signal)


WF1 Pin 4 of CN302




WF5 Pin 17 of CN302




WF2 Pin 8 of CN302




WF6 Pin 19 of CN302




WF3 Pin 6 of CN302



WF7 Pin 13 of CN302



WF4 Pin 15 of CN302





Victor Company of Japan, Limited

Display Division 12, 3-chome, Moriya-cho, Kanagawa-ku, Yokohama-city, Kanagawa-prefecture, 221-8528, Japan

(No.YA713<Rev.001>)

Printed in Japan
VSE