

PHILIPS

32" LCD TV chassis PL13.8

Service Manual

Contents

TYPE A

| | | |
|--------------|---------|------------------------|
| 32PFL3508/F7 | PHILIPS | (Serial No.: ME1) |
| 32PFL3508/F8 | PHILIPS | (Serial No.: XA1, XA2) |
| 32PFL1508/F8 | PHILIPS | (Serial No.: XA1) |

TYPE B


| | | |
|--------------|---------|-------------------|
| 32PFL1508/F8 | PHILIPS | (Serial No.: DS1) |
|--------------|---------|-------------------|

This service manual contains information of different types of models.
Make sure to refer to the section describing your model.

© 2013 Funai Electric Co., Ltd.

All rights reserved. No part of this manual may be reproduced, copied, transmitted, disseminated, transcribed, downloaded or stored in any storage medium, in any form or for any purpose without the express prior written consent of Funai. Furthermore, any unauthorized commercial distribution of this manual or any revision hereto is strictly prohibited.

Information in this document is subject to change without notice. Funai reserves the right to change the content herein without the obligation to notify any person or organization of such changes.

FUNAI with the  design is a registered trademark of Funai Electric Co., Ltd and may not be used in any way without the express written consent of Funai. All other trademarks used herein remain the exclusive property of their respective owners. Nothing contained in this manual should be construed as granting, by implication or otherwise, any license or right to use any of the trademarks displayed herein. Misuse of any trademarks or any other content in this manual is strictly prohibited. Funai shall aggressively enforce its intellectual property rights to the fullest extent of the law.

IMPORTANT SAFETY NOTICE

Proper service and repair is important to the safe, reliable operation of all P&F Equipment. The service procedures recommended by P&F and described in this service manual are effective methods of performing service operations. Some of these service special tools should be used when and as recommended.

It is important to note that this service manual contains various CAUTIONS and NOTICES which should be carefully read in order to minimize the risk of personal injury to service personnel. The possibility exists that improper service methods may damage the equipment. It also is important to understand that these CAUTIONS and NOTICES ARE NOT EXHAUSTIVE. P&F could not possibly know, evaluate and advise the service trade of all conceivable ways in which service might be done or of the possible hazardous consequences of each way. Consequently, P&F has not undertaken any such broad evaluation. Accordingly, a servicer who uses a service procedure or tool which is not recommended by P&F must first use all precautions thoroughly so that neither his safety nor the safe operation of the equipment will be jeopardized by the service method selected.

| |
|---|
| <p>The LCD panel is manufactured to provide many years of useful life. Occasionally a few non active pixels may appear as a tiny spec of color. This is not to be considered a defect in the LCD screen.</p> |
|---|

TABLE OF CONTENTS

| | |
|--|------|
| Specifications | 1-1 |
| Important Safety Precautions | 2-1 |
| Standard Notes for Servicing | 3-1 |
| Cabinet Disassembly Instructions | 4-1 |
| Electrical Adjustment Instructions | 5-1 |
| How to Initialize the LCD TV | 6-1 |
| Firmware Renewal Mode | 7-1 |
| Troubleshooting | 8-1 |
| Block Diagrams | 9-1 |
| Schematic Diagrams / CBA and Test Points | 10-1 |
| Wiring Diagrams | 11-1 |
| Exploded Views | 12-1 |
| Parts List | 13-1 |
| Revision History | 14-1 |

SPECIFICATIONS

< TUNER / NTSC >

| Description | Condition | Unit | Nominal | Limit |
|------------------------|-----------|------|---------|-------|
| 1. AFT Pull-In Range | --- | MHz | ±2.3 | ±2.1 |
| 2. Synchronizing Sens. | TV.ch.4 | dBμ | 18 | 20 |
| | CA.ch.31 | dBμ | 18 | 20 |
| | CA.ch.87 | dBμ | 18 | 23 |

< TUNER / ATSC >

| Description | Condition | Unit | Nominal | Limit |
|-----------------------------------|-----------|------|---------|--------|
| 1. Received Freq. Range (-28dBm) | --- | kHz | --- | ±100 |
| 2. ATSC Dynamic Range (min / max) | ch.4 | dBm | --- | -76/0 |
| | ch.10 | dBm | --- | -76/0 |
| | ch.41 | dBm | --- | -76/+4 |

< LCD PANEL >

| Description | Condition | Unit | Nominal | Limit |
|----------------------------|------------|-------------------|------------------------------|-------|
| 1. Native Pixel Resolution | Horizontal | pixels | 1366 | --- |
| | Vertical | pixels | 768 | --- |
| 2. Brightness (w / filter) | --- | cd/m ² | 250 (TYPE A) 230 (TYPE B) | --- |
| 3. Viewing Angle | Horizontal | ° | -88 to 88 | --- |
| | Vertical | ° | -88 to 88 | --- |

< VIDEO >

| Description | Condition | Unit | Nominal | Limit |
|---------------------------------|---|------|---------|-------|
| 1. Over Scan | Horizontal | % | 5 | 5±5 |
| | Vertical | % | 5 | 5±5 |
| 2. Color Temperature | --- | °K | 12000 | --- |
| | x | | 0.272 | ±3% |
| | y | | 0.278 | ±3% |
| | <Measurement Condition> Input signal: HDMI1 Raster (40/80IRE) 1080i@60 Measurement point: Screen Center Measuring instrument: Made of KONICA MINOLTA Luminance meter CA-310 Aging Time: 60min. (Retail MODE/100IRE Raster HDMI 1080i@60) MODE setting of TV: Shipment setting/Retail MODE Ambient temperature: 25°C ± 5°C | | | |
| | | | | |
| 3. Resolution (composite video) | Horizontal | line | 400 | --- |
| | Vertical | line | 350 | --- |

< AUDIO >

All items are measured across 8 Ω load at speaker output terminal with L.P.F.

| Description | Condition | Unit | Nominal | Limit |
|----------------------------------|----------------|------|------------|------------|
| 1. Audio MAX Output (ATSC 0dBfs) | Lch/Rch | W | 8.0/8.0 | 7.0/7.0 |
| 2. Audio Distortion (NTSC) | 500mW: Lch/Rch | % | 0.5/0.5 | 2.0/2.0 |
| 3. Audio Freq. Response (NTSC) | -6dB: Lch | Hz | 70 to 10 k | 100 to 8 k |
| | -6dB: Rch | Hz | 70 to 10 k | 100 to 8 k |

IMPORTANT SAFETY PRECAUTIONS

Prior to shipment from the factory, our products are strictly inspected for recognized product safety and electrical codes of the countries in which they are to be sold. However, in order to maintain such compliance, it is equally important to implement the following precautions when a set is being serviced.


Safety Precautions for LCD TV Circuit

1. **Before returning an instrument to the customer**, always make a safety check of the entire instrument, including, but not limited to, the following items:

- a. Be sure that no built-in protective devices are defective and have been defeated during servicing. (1) Protective shields are provided on this chassis to protect both the technician and the customer. Correctly replace all missing protective shields, including any removed for servicing convenience. (2) When reinstalling the chassis and/or other assembly in the cabinet, be sure to put back in place all protective devices, including but not limited to, nonmetallic control knobs, insulating fishpapers, adjustment and compartment covers/shields, and isolation resistor/capacitor networks. **Do not operate this instrument or permit it to be operated without all protective devices correctly installed and functioning. Servicers who defeat safety features or fail to perform safety checks may be liable for any resulting damage.**
- b. Be sure that there are no cabinet openings through which an adult or child might be able to insert their fingers and contact a hazardous voltage. Such openings include, but are not limited to, (1) spacing between the Liquid Crystal Panel and the cabinet mask, (2) excessively wide cabinet ventilation slots, and (3) an improperly fitted and/or incorrectly secured cabinet back cover.


- c. **Antenna Cold Check** - With the instrument AC plug removed from any AC source, connect an electrical jumper across the two AC plug prongs. Place the instrument AC switch in the on position. Connect one lead of an ohmmeter to the AC plug prongs tied together and touch the other ohmmeter lead in turn to each tuner antenna input exposed terminal screw and, if applicable, to the coaxial connector. If the measured resistance is less than 1.0 megohm or greater than 5.2 megohm, an abnormality exists that must be corrected before the instrument is returned to the customer. Repeat this test with the instrument AC switch in the off position.

- d. **Leakage Current Hot Check** - With the instrument completely reassembled, plug the AC line cord directly into a 120 V AC outlet. (Do not use an isolation transformer during this test.) Use a leakage current tester or a metering system that complies with American National Standards Institute (ANSI) C101.1 Leakage Current for Appliances and Underwriters Laboratories (UL) 1410, (50.7). With the instrument AC switch first in the on position and then in the off position, measure from a known earth ground (metal water pipe, conduit, etc.) to all exposed metal parts of the instrument (antennas, handle brackets, metal cabinet, screw heads, metallic overlays, control shafts, etc.), especially any exposed metal parts that offer an electrical return path to the chassis. Any current measured must not exceed 0.5 milli-ampere. Reverse the instrument power cord plug in the outlet and repeat the test.



ANY MEASUREMENTS NOT WITHIN THE LIMITS SPECIFIED HEREIN INDICATE A POTENTIAL SHOCK HAZARD THAT MUST BE ELIMINATED BEFORE RETURNING THE INSTRUMENT TO THE CUSTOMER OR BEFORE CONNECTING THE ANTENNA OR ACCESSORIES.

2. Read and comply with all caution and safety-related notes on or inside the receiver cabinet, on the receiver chassis, or on the Liquid Crystal Panel.

3. **Design Alteration Warning** - Do not alter or add to the mechanical or electrical design of this TV receiver. Design alterations and additions, including, but not limited to circuit modifications and the addition of items such as auxiliary audio and/or video output connections, might alter the safety characteristics of this receiver and create a hazard to the user. Any design alterations or additions will void the manufacturer's warranty and may make you, the servicer, responsible for personal injury or property damage resulting therefrom.
4. **Hot Chassis Warning** -
 - a. Some TV receiver chassis are electrically connected directly to one conductor of the AC power cord and maybe safety-serviced without an isolation transformer only if the AC power plug is inserted so that the chassis is connected to the ground side of the AC power source. To confirm that the AC power plug is inserted correctly, with an AC voltmeter, measure between the chassis and a known earth ground. If a voltage reading in excess of 1.0 V is obtained, remove and reinsert the AC power plug in the opposite polarity and again measure the voltage potential between the chassis and a known earth ground.
 - b. Some TV receiver chassis normally have 85V AC(RMS) between chassis and earth ground regardless of the AC plug polarity. This chassis can be safety-serviced only with an isolation transformer inserted in the power line between the receiver and the AC power source, for both personnel and test equipment protection.
 - c. Some TV receiver chassis have a secondary ground system in addition to the main chassis ground. This secondary ground system is not isolated from the AC power line. The two ground systems are electrically separated by insulation material that must not be defeated or altered.
5. Observe original lead dress. Take extra care to assure correct lead dress in the following areas: a. near sharp edges, b. near thermally hot parts-be sure that leads and components do not touch thermally hot parts, c. the AC supply, d. high voltage, and, e. antenna wiring. Always inspect in all areas for pinched, out of place, or frayed wiring. Check AC power cord for damage.
6. Components, parts, and/or wiring that appear to have overheated or are otherwise damaged should be replaced with components, parts, or wiring that meet original specifications. Additionally, determine the cause of overheating and/or damage and, if necessary, take corrective action to remove any potential safety hazard.
7. **Product Safety Notice** - Some electrical and mechanical parts have special safety-related characteristics which are often not evident from visual inspection, nor can the protection they give necessarily be obtained by replacing them with components rated for higher voltage, wattage, etc. Parts that have special safety characteristics are identified by a  on schematics and in parts lists. Use of a substitute replacement that does not have the same safety characteristics as the recommended replacement part might create shock, fire, and/or other hazards. The product's safety is under review continuously and new instructions are issued whenever appropriate. Prior to shipment from the factory, our products are strictly inspected to confirm they comply with the recognized product safety and electrical codes of the countries in which they are to be sold. However, in order to maintain such compliance, it is equally important to implement the following precautions when a set is being serviced.

Precautions during Servicing

- A.** Parts identified by the **▲** symbol are critical for safety.
Replace only with part number specified.
- B.** In addition to safety, other parts and assemblies are specified for conformance with regulations applying to spurious radiation. These must also be replaced only with specified replacements.
Examples: RF converters, RF cables, noise blocking capacitors, and noise blocking filters, etc.
- C.** Use specified internal wiring. Note especially:
 - 1) Wires covered with PVC tubing
 - 2) Double insulated wires
 - 3) High voltage leads
- D.** Use specified insulating materials for hazardous live parts. Note especially:
 - 1) Insulation Tape
 - 2) PVC tubing
 - 3) Spacers
 - 4) Insulators for transistors.
- E.** When replacing AC primary side components (transformers, power cord, etc.), wrap ends of wires securely about the terminals before soldering.
- F.** Observe that the wires do not contact heat producing parts (heat sinks, oxide metal film resistors, fusible resistors, etc.)
- G.** Check that replaced wires do not contact sharp edged or pointed parts.
- H.** When a power cord has been replaced, check that 11~13 lb (5~6 kg) of force in any direction will not loosen it.
- I.** Also check areas surrounding repaired locations.
- J.** Use care that foreign objects (screws, solder droplets, etc.) do not remain inside the set.
- K.** When connecting or disconnecting the internal connectors, first, disconnect the AC plug from the AC supply outlet.
- L.** When installing parts or assembling the cabinet parts, be sure to use the proper screws and tighten certainly.

Safety Check after Servicing

Examine the area surrounding the repaired location for damage or deterioration. Observe that screws, parts and wires have been returned to original positions. Afterwards, perform the following tests and confirm the specified values in order to verify compliance with safety standards.

1. Clearance Distance

When replacing primary circuit components, confirm specified clearance distance (d) and (d') between soldered terminals, and between terminals and surrounding metallic parts. (See Fig. 1)

Table 1: Ratings for selected area

| AC Line Voltage | Region | Clearance Distance (d), (d') |
|-----------------|------------------|--------------------------------------|
| 110 to 130 V | U.S.A. or Canada | ≥ 3.2 mm (0.126 inches) |

Note: This table is unofficial and for reference only. Be sure to confirm the precise values.




Fig. 1

2. Leakage Current Test

Confirm the specified (or lower) leakage current between B (earth ground, power cord plug prongs) and externally exposed accessible parts (RF terminals, antenna terminals, video and audio input and output terminals, microphone jacks, earphone jacks, etc.) is lower than or equal to the specified value in the table below.

Measuring Method: (Power ON)

Insert load Z between B (earth ground, power cord plug prongs) and exposed accessible parts. Use an AC voltmeter to measure across both terminals of load Z . See Fig. 2 and following table.




Fig. 2

Table 2: Leakage current ratings for selected areas


| AC Line Voltage | Region | Load Z | Leakage Current (i) | Earth Ground (B) to: |
|-----------------|------------------|---|-------------------------|--------------------------|
| 110 to 130 V | U.S.A. or Canada | $0.15 \mu F$ CAP. & $1.5 k\Omega$ RES. Connected in parallel | $i \leq 0.5$ mA rms | Exposed accessible parts |

Note: This table is unofficial and for reference only. Be sure to confirm the precise values.


STANDARD NOTES FOR SERVICING

Circuit Board Indications


1. The output pin of the 3 pin Regulator ICs is indicated as shown.



2. For other ICs, pin 1 and every fifth pin are indicated as shown.




3. The 1st pin of every male connector is indicated as shown.



Pb (Lead) Free Solder

Pb free mark will be found on PCBs which use Pb free solder. (Refer to figure.) For PCBs with Pb free mark, be sure to use Pb free solder. For PCBs without Pb free mark, use standard solder.



Pb free mark

How to Remove / Install Flat Pack-IC

1. Removal

With Hot-Air Flat Pack-IC Desoldering Machine:

1. Prepare the hot-air flat pack-IC desoldering machine, then apply hot air to the Flat Pack-IC (about 5 to 6 seconds). (Fig. S-1-1)





Fig. S-1-1

2. Remove the flat pack-IC with tweezers while applying the hot air.
3. Bottom of the flat pack-IC is fixed with glue to the CBA; when removing entire flat pack-IC, first apply soldering iron to center of the flat pack-IC and heat up. Then remove (glue will be melted). (Fig. S-1-6)
4. Release the flat pack-IC from the CBA using tweezers. (Fig. S-1-6)

CAUTION:


1. The Flat Pack-IC shape may differ by models. Use an appropriate hot-air flat pack-IC desoldering machine, whose shape matches that of the Flat Pack-IC.
2. Do not supply hot air to the chip parts around the flat pack-IC for over 6 seconds because damage to the chip parts may occur. Put masking tape around the flat pack-IC to protect other parts from damage. (Fig. S-1-2)

3. The flat pack-IC on the CBA is affixed with glue, so be careful not to break or damage the foil of each pin or the solder lands under the IC when removing it.




With Soldering Iron:

1. Using desoldering braid, remove the solder from all pins of the flat pack-IC. When you use solder flux which is applied to all pins of the flat pack-IC, you can remove it easily. (Fig. S-1-3)



2. Lift each lead of the flat pack-IC upward one by one, using a sharp pin or wire to which solder will not adhere (iron wire). When heating the pins, use a fine tip soldering iron or a hot air desoldering machine. (Fig. S-1-4)





3. Bottom of the flat pack-IC is fixed with glue to the CBA; when removing entire flat pack-IC, first apply soldering iron to center of the flat pack-IC and heat up. Then remove (glue will be melted). (Fig. S-1-6)
4. Release the flat pack-IC from the CBA using tweezers. (Fig. S-1-6)

With Iron Wire:



1. Using desoldering braid, remove the solder from all pins of the flat pack-IC. When you use solder flux which is applied to all pins of the flat pack-IC, you can remove it easily. (Fig. S-1-3)
2. Affix the wire to a workbench or solid mounting point, as shown in Fig. S-1-5.
3. While heating the pins using a fine tip soldering iron or hot air blower, pull up the wire as the solder melts so as to lift the IC leads from the CBA contact pads as shown in Fig. S-1-5.
4. Bottom of the flat pack-IC is fixed with glue to the CBA; when removing entire flat pack-IC, first apply soldering iron to center of the flat pack-IC and heat up. Then remove (glue will be melted). (Fig. S-1-6)
5. Release the flat pack-IC from the CBA using tweezers. (Fig. S-1-6)

Note: When using a soldering iron, care must be taken to ensure that the flat pack-IC is not being held by glue. When the flat pack-IC is removed from the CBA, handle it gently because it may be damaged if force is applied.



2. Installation

1. Using desoldering braid, remove the solder from the foil of each pin of the flat pack-IC on the CBA so you can install a replacement flat pack-IC more easily.
2. The "●" mark on the flat pack-IC indicates pin 1. (See Fig. S-1-7.) Be sure this mark matches the pin 1 on the PCB when positioning for installation. Then presolder the four corners of the flat pack-IC. (See Fig. S-1-8.)
3. Solder all pins of the flat pack-IC. Be sure that none of the pins have solder bridges.



Instructions for Handling Semi-conductors



Electrostatic breakdown of the semi-conductors may occur due to a potential difference caused by electrostatic charge during unpacking or repair work.

1. Ground for Human Body

Be sure to wear a grounding band ($1\text{ M}\Omega$) that is properly grounded to remove any static electricity that may be charged on the body.

2. Ground for Workbench

Be sure to place a conductive sheet or copper plate with proper grounding ($1\text{ M}\Omega$) on the workbench or other surface, where the semi-conductors are to be placed. Because the static electricity charge on clothing will not escape through the body grounding band, be careful to avoid contacting semi-conductors with your clothing.



CABINET DISASSEMBLY INSTRUCTIONS


Screw Torque Specification

| Ref. No. | Part Number | Part Name | Tightening Torque |
|----------|-------------|---|-------------------------|
| L4 | GBHP3080 | SCREW P-TIGHT (M3X8 BIND HEAD+BLK) | 5.2±0.9lb-in |
| L23 | GBJS3060 | SCREW S-TIGHT (M3X6 BIND HEAD+) | |
| L24 | GBHS3060 | S-TIGHT SCREW (M3X6 BIND HEAD+BLACK) | |
| SSK1 | 1ESA34670 | STAND SCREW KIT (SCREW P-TIGHT M4X14 BIND HEAD+BLK) | (approx. 8.7±0.9lb-in)* |

* For reference

1. Disassembly Flowchart

This flowchart indicates the disassembly steps for the cabinet parts and the CBA in order to gain access to items to be serviced. When reassembling, follow the steps in reverse order. Bend, route and dress the cables as they were.



2. Disassembly Method

| Step/ Loc. No. | Part | Fig. No. | Removal | Note |
|----------------|----------------|----------|----------------|------|
| [1] | Rear Cover | D1 | 7(S-1), 5(S-2) | --- |
| [2] | Stand Assembly | D1 | 3(S-3) | --- |
| [3] | Speaker | D2 D5 | CN3801 | --- |
| [4] | Bottom Cover | D2 | 4(S-4) | 1 |

| Step/ Loc. No. | Part | Fig. No. | Removal | Note |
|----------------|-----------------------|----------|--|------|
| [5] | Power Supply CBA | D3 D5 | 4(S-5), CN501, CN601, CN1001 | --- |
| [6] | Digital Main CBA Unit | D3 D5 | 4(S-6), CN3013*1, CN3006*2 CN3101, Jack Holder | --- |
| [7] | LCD Panel Assembly | D3 | ----- | --- |
| [8] | Front Cabinet | D4 | 8(S-7), Decoration Plate*3 | 2 |
| [9] | Function CBA Unit | D4 | Sensor Lens, Shield Plate, Control Plate | 2 |

↓
(1)

↓
(2)

↓
(3)

↓
(4)

↓
(5)

*1: TYPE A models

*2: TYPE B models

*3: 32PFL3508 models

Note:

- (1) Order of steps in procedure. When reassembling, follow the steps in reverse order. These numbers are also used as the Identification (location) No. of parts in figures.
- (2) Parts to be removed or installed.
- (3) Fig. No. showing procedure of part location
- (4) Identification of parts to be removed, unhooked, unlocked, released, unplugged, unclamped, or desoldered.
P = Spring, L = Locking Tab, S = Screw,
H = Hex Screw, CN = Connector
e.g. 2(S-2) = two Screws of (S-2),
2(L-2) = two Locking Tabs of (L-2)
- (5) Refer to the following "Reference Notes in the Table."

Important Precautions concerning the LCD Panel Assembly:

1. When you disassemble/re-assemble the Bottom Cover for 32PFL3508/F8 (Serial No.: XA2) model.

- The CBA which is connected to the Digital Main CBA Unit with CL3006 cannot be replaced alone. This CBA can only be supplied as LCD Panel

Assembly. Be careful not to touch this CBA unnecessarily.

2. When you disassemble/re-assemble the Front Cabinet or Function CBA Unit

- Be careful not to break the hooks. If you pull with too much force, the hooks may be damaged.
- Be careful not to scratch the display panel when assembling.
- Be careful not to scratch the rear frame when disassembling/re-assembling or when tightening the screws.
- Make sure the Shield Plate is placed properly.
- The Function CBA Unit and Sensor Lens are fixed in place by the hooks. Make sure these hooks are not damaged. Make sure the Function CBA Unit and Sensor Lens are securely in place when re-assembling.
- The screw tightening torque must be 5.2lb-in (6kgf·cm).
- Make sure the tact switches operate normally after replacing the Front Cabinet, Function CBA Unit, Sensor Lens, or Shield Plate.
- Make sure to replace the Control Plate and Decoration Plate to a new one when replacing the Front Cabinet.







Fig. D1




*1: For 32PFL3508/F8 (Serial No.:XA2) model, make sure to read the precautions on pages 4-1 and 4-2 when you disassemble/re-assemble the Bottom Cover.





*2: Make sure to read all the precautions on page 4-2 when you disassemble/re-assemble the Front Cabinet or Function CBA Unit.

TV Cable Wiring Diagram



ELECTRICAL ADJUSTMENT INSTRUCTIONS

General Note: “CBA” is abbreviation for “Circuit Board Assembly.”

Note: Electrical adjustments are required after replacing circuit components and certain mechanical parts. It is important to perform these adjustments only after all repairs and replacements have been completed.
Also, do not attempt these adjustments unless the proper equipment is available.

Test Equipment Required

1. Remote control unit
2. Color Analyzer,
CA-310 (KONICA MINOLTA Luminance meter) or
measuring instrument as good as CA-310.

How to set up the service mode:

Service mode:

1. Turn the power on.
2. Press [MENU] button to display Setup menu.
3. Select “Features”.
4. Select “Software Upgrade”.
5. Select “Current Software Info”.
6. Press [0], [6], [2], [5], [9], [6] and [INFO] buttons on the remote control unit in this order. The following screen appears.

“*” differs depending on the models.

| | |
|--------------------|--------------------------------|
| Code: | *****_**_*_*_*_*_*_*_** |
| Pic code: | ***_*****_***_*_*_*_*_** |
| Panel-Option code: | **_*_*_*_*_*_*_*_*_*_*_*_*_*_* |
| MIPS: | Push 0 key |


Press "POWER" key to exit.

| | | | |
|-------------------|------------|-------------------|-------|
| Safety: | Safety_Non | | |
| HDMI EDID: | ** | | |
| HDMI UART: | OFF | Total Watch Time: | ***** |
| Touch Sensor Ver: | -.-- / --- | Lightsensor: | ** |

1. Purity Check Mode

This mode cycles through full-screen displays of red, green, blue, and white to check for non-active pixels.

1. Enter the service mode.
2. Each time the [7] button on the remote control unit is pressed, the display changes as follows.




3. To cancel or to exit from the Purity Check Mode, press [CH RETURN] or [PREV CH] button.

The VCOM Adjustment should be performed when replacing the Digital Main CBA for 32PFL1508/F8 (Serial No.: DS1).

2. VCOM Adjustment

| Test Point | Adj. Point |
|----------------|---------------------------|
| Screen | [CHANNEL UP/DOWN] buttons |
| M. EQ. | Spec. |
| Color analyzer | See below |

Figure



1. Operate the unit for more than 60 minutes.
2. Set the color analyzer at the zero point calibration and bring the optical receptor pointing at the center of the LCD-Panel.
Note: The optical receptor must be set perpendicular to the LCD Panel surface.
3. Enter the service mode.
4. Press [2] button on the remote control unit.
5. Press [CHANNEL UP/DOWN] buttons on the remote control unit so that the color analyzer value becomes minimum.
6. To cancel or to exit from the VCOM Adjustment, press [CH RETURN] or [PREV CH] button.

The White Balance Adjustment should be performed when replacing the LCD Panel or Digital Main CBA.


3. White Balance Adjustment

Purpose: To mix red and blue beams correctly for pure white.

Symptom of Misadjustment: White becomes bluish or reddish.

| ITEM | SPECIFICATION |
|---------------------|--|
| Color temperature | $x = 0.272 \pm 0.003$ $y = 0.278 \pm 0.003$ |
| Input Signal | Internal pattern (40/80% raster) |
| Measurement point | Screen center |
| M. EQ. | CA-310 (KONICA MINOLTA Luminance meter) or measuring instrument as good as CA-310. |
| Aging time | 60min. (Retail MODE/100IRE Raster HDMI 1080i@60) |
| MODE setting of TV | Shipment setting/ Retail MODE |
| Ambient temperature | $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ |


1. Operate the unit for more than 60 minutes.
2. Enter the service mode.
3. Press [VOLUME DOWN] button three times on the remote control unit to select "Drive setting" mode. "Drive" appears in the screen.
4. Set the color analyzer at the CHROMA mode and zero point calibration. Bring the optical receptor pointing at the center of the LCD-Panel.




Note: The optical receptor must be set perpendicularly to the LCD Panel surface.

5. Press [3] button to select the "HDB" for High Drive Blue adjustment. ("HDB" appears in the screen.)

6. Press [MENU] button. The internal Raster signal appears in the screen. ("Internal (Single)" appears in the upper right of the screen as shown below.)



7. Press [CHANNEL UP/DOWN] buttons to adjust the color temperature becomes 12000°K ($x = 0.272 / y = 0.278 \pm 0.003$).
8. Press [1] button to select the "HDR" for High Drive Red adjustment ("HDR" appears in the screen.) and press [CHANNEL UP/DOWN] buttons to adjust the color temperature.
9. If necessary, adjust the "HDB" or "HDR" again.
10. Press [6] button to select the "LDB" for Low Drive Blue adjustment ("LDB" appears in the screen.) and press [CHANNEL UP/DOWN] buttons to adjust the color temperature.



11. Press [4] button to select the "LDR" for Low Drive Red adjustment ("LDR" appears in the screen.) and press [CHANNEL UP/DOWN] buttons to adjust the color temperature.
12. If necessary, adjust the "LDB" or "LDR" again.
13. Press [VOLUME DOWN] button to shift to the "Debugging Message" mode.
If there is no message under "[WB]" section, this adjustment completes.
If "Drive settings are NG. Retry again." is displayed, repeat above steps from 5. to 12. Then check "Debugging Message" again. If "Drive settings are NG. Retry again." is displayed, replace the LCD Panel or Digital Main CBA.
14. To cancel or to exit from the White Balance Adjustment, press [CH RETURN] or [PREV CH] button.

HOW TO INITIALIZE THE LCD TV

The purpose of initialization is to place the set in a new out of box condition. The customer will be prompted to select a language and program channels after the set has been initialized.

To put the program back at the factory-default, initialize the LCD TV using the following procedure.

NOTE: Disconnect any device from the USB Port before you conduct on this procedure.

1. Turn the power on.
2. Enter the service mode.
 - To cancel the service mode, press [⏻] button on the remote control unit.
3. Press [BACK] button to enter the Panel Key Confirmation Menu.
4. Press any button on the control panel.
5. Press [INFO] button to proceed with the self check mode.
6. Make sure to confirm the "INITIALIZED FINISH" appears in the green screen.
7. Unplug the AC Cord and plug it back on again.

FIRMWARE RENEWAL MODE

Equipment Required

- a. USB storage device
- b. Remote Control Unit

Firmware Update Procedure

User Upgrade (Filename example: TVNB012_00_PF_XX91_AC.ecc)


Upgrade the firmware only. The setting values will not be initialized.

The User Upgrade and the Firmware Upgrade (Factory Upgrade) will be done by the same file. If you want to upgrade the firmware and initialize the setting values also, add "FACT_" at the beginning of the filename.

If you want to upgrade the firmware only and leave the setting values as they are, eliminate the "FACT_" from the filename.

Update procedure


1. Turn the power on.
2. Press [MENU] button to display Menu.
3. Select "Features".
4. Select "Software Upgrade".
5. Select "Upgrade" to display Upgrade screen.
6. Press [OK] button to display Software Upgrade screen.
7. Select "USB" and press [OK] button.
8. Insert the USB storage device to the USB port as shown below.



9. Select "Check" and press [OK] button.
10. Select "Upgrade" and press [OK] button to start software upgrade.

11. The update will start and the following will appear in the screen.

"*" differs depending on the models.




Note: If the above screen isn't displayed, repeat from step 1.

The appearance shown in *1 is described as follows.

| Appearance | State |
|----------------|---|
| Downloading... | Downloading the firmware from the USB storage device. |
| Writing... | Writing the downloaded firmware in flash memory. |
| Checking... | Checking the new firmware. |

12. When the firmware update is completed, the following will appear in the screen.



Remove the USB storage device from the USB port.
Turn the power off and turn the power on again.

Factory Upgrade (Firmware Upgrade/Flash Upgrade)

Firmware Upgrade (Filename example: FACT_TVNB012_00_PF_XX91_AC.ecc)

Upgrade the firmware and initialize the setting values.

The User Upgrade and the Firmware Upgrade (Factory Upgrade) will be done by the same file. If you want to upgrade the firmware and initialize the setting values also, add "FACT_" at the beginning of the filename.

If you want to upgrade the firmware only and leave the setting values as they are, eliminate the "FACT_" from the filename.

Flash Upgrade (Filename example: ALL_TVNB012_00_PF_XX91_AC.ecc)

Upgrade the firmware and initialize the setting values along with the factory default such as White Balance, etc.


Before the upgrade, you will need to make a note of all the factory default so you will be able to set it back on the TV after the initialization.

The Flash Upgrade will be done by it's unique file.

The User Upgrade/Firmware Upgrade (Factory Upgrade) file cannot be used for this upgrade.


Update procedure

1. Turn the power off.
2. Insert the USB storage device to the USB port as shown below.



3. Turn the power on.
4. The update will start and the following will appear in the screen.

"*" differs depending on the models.




Note: If the above screen isn't displayed, repeat from step 1.

The appearance shown in *1 is described as follows.

| Appearance | State |
|----------------|---|
| Downloading... | Downloading the firmware from the USB storage device. |
| Writing... | Writing the downloaded firmware in flash memory. |
| Checking... | Checking the new firmware. |

5. When the firmware update is completed, the following will appear in the screen.



Remove the USB storage device from the USB port.

Turn the power off and turn the power on again.


Service mode initial screen with a word "INITIALIZED" will appear in the screen. The color of the word "INITIALIZED" will change from red to green when initialization is completed.

TROUBLESHOOTING


Note: This Troubleshooting section covers the entire PL13.8 chassis models. Thus some Reference number of parts shown below may not be used depending on the model. Please refer to the parts list for each model.

[Power Supply Section]


FLOW CHART NO.1




FLOW CHART NO.2




FLOW CHART NO.3




FLOW CHART NO.4




FLOW CHART NO.5



FLOW CHART NO.6




FLOW CHART NO.7




[Video Signal Section]


FLOW CHART NO.1



FLOW CHART NO.2




FLOW CHART NO.3




[Audio Signal Section]

FLOW CHART NO.1




BLOCK DIAGRAMS


1. System Control Block Diagram




2. Video/Audio Block Diagram




3. Digital Signal Process Block Diagram [TYPE A]




3. Digital Signal Process Block Diagram [TYPE B]



4. LED Backlight Drive Block Diagram



5. Power Supply Block Diagram



SCHEMATIC DIAGRAMS / CBA AND TEST POINTS

Standard Notes

WARNING

Many electrical and mechanical parts in this chassis have special characteristics. These characteristics often pass unnoticed and the protection afforded by them cannot necessarily be obtained by using replacement components rated for higher voltage, wattage, etc. Replacement parts that have these special safety characteristics are identified in this manual and its supplements; electrical components having such features are identified by the mark “▲” in the schematic diagram and the parts list. Before replacing any of these components, read the parts list in this manual carefully. The use of substitute replacement parts that do not have the same safety characteristics as specified in the parts list may create shock, fire, or other hazards.

Notes:

1. Do not use the part number shown on these drawings for ordering. The correct part number is shown in the parts list, and may be slightly different or amended since these drawings were prepared.
2. All resistance values are indicated in ohms ($K = 10^3$, $M = 10^6$).
3. Resistor wattages are 1/4W or 1/6W unless otherwise specified.
4. All capacitance values are indicated in μF ($P = 10^{-6} \mu F$).
5. All voltages are DC voltages unless otherwise specified.
6. This schematic diagrams are masterized version that should cover the entire PL13.8 chassis models. Thus some parts in detail illustrated on this schematic diagrams may vary depend on the model within the PL13.8 chassis. Please refer to the parts lists for each models.
7. The Circuit Board layout illustrated on this service manual is the latest version for this chassis at the moment of making this service manual. Depend on the mass production date of each model, the actual layout of each Board may differ slightly from this version.

LIST OF CAUTION, NOTES, AND SYMBOLS USED IN THE SCHEMATIC DIAGRAMS ON THE FOLLOWING PAGES:

1. CAUTION:

CAUTION: FOR CONTINUED PROTECTION AGAINST RISK OF FIRE, REPLACE ONLY WITH SAME TYPE_A,_V FUSE.

ATTENTION: UTILISER UN FUSIBLE DE RECHANGE DE MÊME TYPE DE_A,_V.

2. CAUTION:

Fixed Voltage (or Auto voltage selectable) power supply circuit is used in this unit.


If Main Fuse (F602) is blown, first check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply. Otherwise it may cause some components in the power supply circuit to fail.

3. Note:

- Do not use the part number shown on the drawings for ordering. The correct part number is shown in the parts list, and may be slightly different or amended since the drawings were prepared.
- To maintain original function and reliability of repaired units, use only original replacement parts which are listed with their part numbers in the parts list section of the service manual.

4. Voltage indications on the schematics are as shown below:

Plug the TV power cord into a standard AC outlet.:




5. How to read converged lines

1-D3

 Distinction Area
 Line Number
 (1 to 3 digits)

Examples:

- "1-D3" means that line number "1" goes to the line number "1" of the area "D3".
- "1-B1" means that line number "1" goes to the line number "1" of the area "B1".



6. Test Point Information

: Indicates a test point with a jumper wire across a hole in the PCB.

: Used to indicate a test point with a component lead on foil side.


: Used to indicate a test point with no test pin.

: Used to indicate a test point with a test pin.

The reference number of parts on Schematic Diagrams/CBA can be retrieved by application search function.


Power Supply Schematic Diagram [TYPE A]

CAUTION !
Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit.
If Main Fuse (F602) is blown , check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply.
Otherwise it may cause some components in the power supply circuit to fail.



CAUTION ! : For continued protection against risk of fire,
replace only with same type 2.5A, 250V fuse.
ATTENTION : Utiliser un fusible de rechange de même type de 2.5A, 250V.


NOTE:
The voltage for parts in hot circuit is measured using
hot GND as a common terminal.



Power Supply Schematic Diagram [TYPE B]

CAUTION !

Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit. If Main Fuse (F602) is blown, check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply. Otherwise it may cause some components in the power supply circuit to fail.




CAUTION !: For continued protection against risk of fire, replace only with same type 2.5A, 250V fuse.


ATTENTION : Utiliser un fusible de rechange de même type de 2.5A, 250V.

NOTE:

The voltage for parts in hot circuit is measured using hot GND as a common terminal.



Function Schematic Diagram




Digital Main 1 Schematic Diagram [TYPE A]

***1 NOTE:**

The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




Digital Main 2 Schematic Diagram [TYPE A]

***1 NOTE:**

The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




1

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




1

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.



A vertical axis with tick marks labeled 1, 2, 3, and 4 from bottom to top.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




Digital Main 6 Schematic Diagram [TYPE A]

***1 NOTE:**

The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




Digital Main 1 Schematic Diagram [TYPE B]

***1 NOTE:**


The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.



Digital Main 2 Schematic Diagram [TYPE B]

*1 NOTE:
The order of pins shown in this diagram is different from that of actual IC3005.
IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.



4

3

2




Digital Main 4 Schematic Diagram [TYPE B]

***1 NOTE:**

The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




Digital Main 5 Schematic Diagram [TYPE B]

***1 NOTE:**

The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.




Digital Main 6 Schematic Diagram [TYPE B]

***1 NOTE:**


The order of pins shown in this diagram is different from that of actual IC3005.

IC3005 is divided into six and shown as IC3005 (1/6) ~ IC3005 (6/6) in this Digital Main Schematic Diagram Section.



Power Supply CBA Top View [TYPE A]


CAUTION !
Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit.
If Main Fuse (F602) is blown , check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply.
Otherwise it may cause some components in the power supply circuit to fail.



CAUTION ! : For continued protection against risk of fire,
replace only with same type 2.5A, 250V fuse.
ATTENTION : Utiliser un fusible de rechange de même type de 2.5A, 250V.


Because a hot chassis ground is present in the power supply circuit, an isolation transformer must be used when repairing.
Also, in order to have the ability to increase the input slowly, when troubleshooting this type of power supply circuit, a variable isolation transformer is required.

NOTE:
The voltage for parts in hot circuit is measured using hot GND as a common terminal.



Power Supply CBA Bottom View [TYPE A]


CAUTION !
Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit.
If Main Fuse (F602) is blown , check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply.
Otherwise it may cause some components in the power supply circuit to fail.



CAUTION ! : For continued protection against risk of fire,
replace only with same type 2.5A, 250V fuse.
ATTENTION : Utiliser un fusible de rechange de même type de 2.5A, 250V.

Because a hot chassis ground is present in the power supply circuit, an isolation transformer must be used when repairing.
Also, in order to have the ability to increase the input slowly, when troubleshooting this type of power supply circuit, a variable isolation transformer is required.


NOTE:
The voltage for parts in hot circuit is measured using hot GND as a common terminal.



Power Supply CBA Top View [TYPE B]

CAUTION !

Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit. If Main Fuse (F602) is blown, check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply. Otherwise it may cause some components in the power supply circuit to fail.




CAUTION ! : For continued protection against risk of fire,
replace only with same type 2.5A, 250V fuse.

ATTENTION : Utiliser un fusible de rechange de même type de 2.5A, 250V.

Because a hot chassis ground is present in the power supply circuit, an isolation transformer must be used when repairing. Also, in order to have the ability to increase the input slowly, when troubleshooting this type of power supply circuit, a variable isolation transformer is required.


NOTE:

The voltage for parts in hot circuit is measured using hot GND as a common terminal.



Power Supply CBA Bottom View [TYPE B]


CAUTION !
Fixed voltage (or Auto voltage selectable) power supply circuit is used in this unit.
If Main Fuse (F602) is blown , check to see that all components in the power supply circuit are not defective before you connect the AC plug to the AC power supply.
Otherwise it may cause some components in the power supply circuit to fail.




CAUTION ! : For continued protection against risk of fire,
replace only with same type 2.5A, 250V fuse.
ATTENTION : Utiliser un fusible de rechange de même type de 2.5A, 250V.

Because a hot chassis ground is present in the power supply circuit, an isolation transformer must be used when repairing.
Also, in order to have the ability to increase the input slowly, when troubleshooting this type of power supply circuit, a variable isolation transformer is required.


NOTE:
The voltage for parts in hot circuit is measured using hot GND as a common terminal.




WIRING DIAGRAM



EXPLODED VIEWS




Packing






TYPE A

PARTS LIST [32PFL3508/F8 (Serial No.: XA1)]


Mechanical Parts

PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.


NOTE: Parts that are not assigned part numbers (-----) are not available.

| Ref. No. | Description | Part No. |
|---|--|--------------|
| A3 | REAR COVER A3AF0UT | 1EM030166 |
| A4 | BOTTOM COVER A3AF0UT | 1EM030167A |
| A13 | JACK HOLDER A31M0UT | 1EM334000 |
| A15  | RATING LABEL A3AFEMA | ----- |
| A16 | LOGO LABEL A3AFEMA | ----- |
| AC601  | AC CORD UL/CSA/1680/NO/BLACK | WAC162LTE002 |
| B17 | WALL MOUNT BRACKET A11N0UH | 1EM434637 |
| B18 | WALL MOUNT COVER A2170UT | 1EM332137 |
| B23 | WIRE LABEL A3AF0UT | ----- |
| CL3101 | FFC WIRE ASSEMBLY 9PIN 9PIN/WHITE/184MM | WX1A3AF0S102 |
| CL3701 | FFC WIRE ASSEMBLY 23PIN 23PIN/WHITE/130MM | WX1A3AF0S121 |
| CL3801 | WIRE ASSEMBLY 4PIN 4PIN/320MM&30MM | WX1A3AF0C311 |
| L4 | SCREW P-TIGHT M3X8 BIND HEAD+ BLK | GBHP3080 |
| L23 | SCREW S-TIGHT M3X6 BIND HEAD+ | GBJS3060 |
| L24 | S-TIGHT SCREW M3X6 BIND HEAD+BLACK | GBHS3060 |
| SA1 | STAND ASSEMBLY A20F0PT | 1ESA32345 |
| SP3801 | SPEAKER MAGNETIC 8Ω8W S0310F14 | DS08110XQ002 |
| SP3802 | SPEAKER MAGNETIC 8Ω8W S0310F14 | DS08110XQ002 |
| SSK1 | STAND SCREW KIT A31M0UT(SCREW P-TIGHT M4X14 BIND HEAD+BLK) | 1ESA34004 |
| PACKING | | |
| S1 | CARTON A3AFEMA | 2EMC00096 |
| S3 | STYROFOAM TOP A3AF0UT | 1EM030285 |
| S4 | STYROFOAM BOTTOM A3AF0UT | 1EM030286 |
| S6 | SET BAG A31F0UT | 2EMC00088 |
| S7 | SERIAL NO. LABEL A01PBUH | ----- |
| S12 | CARTON LABEL A3AFEMA | ----- |
| ACCESSORIES | | |
| X1 | POLYETHYLENE BAG HDPE 180X340XT0.03 | 1EM435579 |
| X2  | OWNERS MANUAL A3AFEMA | 2EMN00031A |
| X3 | REMOTE CONTROL UNIT YKF335-001 | URMT39JHG001 |
| X4 | BATTERY R03-B500/01S | XB0M451CZB01 |
| X6 | QUICK START GUIDE A3AFEMA | 2EMN00032A |

LCD PANEL ASSEMBLY

| Ref. No. | Description | Part No. |
|--|--|--------------|
| LCD1  | LCD PANEL ASSEMBLY | U3FF2PA |
| | Consists of the following | |
| A1 | FRONT CABINET A3AFEMA | 2EMM00125 |
| A5 | DECORATION PLATE A3UFZZT | 2EMH00095 |
| A6 | CONTROL PLATE A3UFZZT | 2EMH00096 |
| A9 | SENSOR LENS A3UFZZT | 2EMM00095 |
| B12 | SHIELD PLATE A3UFZZT | 2EMS00072 |
| CL3006 | FFC WIRE ASSEMBLY 30PIN(W/SHIELD) 30P/FFC/SHIELD/500MM | WX1A3AF0P401 |
| L4 | SCREW P-TIGHT M3X8 BIND HEAD+ BLK | GBHP3080 |
| | LCD MODULE | ----- |
| W01 | WIRE ASSEMBLY 2PIN 2PIN/70MM/1PIN-RED | WX1U3FF2-W01 |

Electrical Parts

PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTES:

- Parts that are not assigned part numbers (-----) are not available.
- Tolerance of Capacitors and Resistors are noted with the following symbols.

C.....±0.25% D.....±0.5% F.....±1%
 G.....±2% J.....±5% K.....±10%
 M.....±20% N.....±30% Z.....+80/-20%




DIGITAL MAIN CBA UNIT




| Ref. No. | Description | Part No. |
|----------|--|--------------|
| | DIGITAL MAIN CBA UNIT | A3AFEMMA-001 |
| IC3001 | IC DC-DC CONVERTER MP1472GJC452Z | NSCA0T09M021 |
| IC3002 | IC 512MB DDR2 SDRAM K4T51163QJ-BCE7 | NSCA0R0SM048 |
| IC3003 | IC DC-DC CONVERTER MP1472GJC452Z | NSCA0T09M021 |
| IC3004 | IC REGULATOR BD00IA5WEFJ-E2 | QSCA0T0RM233 |
| IC3005 | IC DTV-C7V R8A05011BG-U0/256FHP | QSAA0R0HT057 |
| IC3006 | IC 32M-BIT SERIAL FLASH MEMORY W25Q32FVSSIG | NSCA0R0ZM018 |
| IC3007 | IC LDO REGULATOR BD00IC0WEFJ-HTSOP-J8 | QSCA0T0RM397 |
| IC3008 | IC DC-DC CONVERTER MP1472GJC452Z | NSCA0T09M021 |
| IC3009 | IC RESET IC-PST8429UR | QSCA0T0MM075 |
| IC3011 | IC EEPROM BU9883FV-WE2 | QSCA0T0RM105 |
| IC3013 | IC SINGLE BUS BUFFER 74LVC1G126GW | NSCA0TNXP004 |
| IC3014 | IC SINGLE BUS BUFFER 74LVC1G126GW | NSCA0TNXP004 |
| IC3018 | IC HDMI SW TMDS351PAGR /PAG-64 | NSCA0T0TY068 |
| IC3019 | IC USB HIGH-SIDE SW AP2151WG-7/SOT25/5PI | NSCA0TDES015 |
| IC3601 | IC REGULATOR AP2121AK-3.3TRE1 | NSCA0TBCD026 |
| IC3621 | IC DC-DC CONVERTER MP1472GJC452Z | NSCA0T09M021 |
| IC3801 | IC D-CLASS AUDIO POWER AMPLIFI TPA3110D2PWPR | NSCA0T0TY073 |
| IC3851 | IC HEADPHONE AMP BH3547F SOP 8PIN | QSZBA0TRM119 |
| TU3901 | TUNER UNIT U9001UT | U9001UT |

FUNCTION CBA UNIT


| Ref. No. | Description | Part No. |
|----------|-------------------|--------------|
| | FUNCTION CBA UNIT | A3AFEMSW-001 |

POWER SUPPLY CBA





| Ref. No. | Description | Part No. |
|--|---|--------------|
| | POWER SUPPLY CBA Consists to the following | A3AF0MPW-001 |
| CAPACITORS | | |
| C602  | SAFTY CAP. 1000pF/250V KX | CA2E102MR101 |
| C603  | SAFTY CAP. 1000pF/250V KX | CA2E102MR101 |
| C604  | CAP METALLIZED FILM 0.22µF/275V/K | CTA224PKR001 |

| Ref. No. | Description | Part No. |
|--|--|--------------|
| C605 | CAP ELE 330µF/200V/M87 | CEB3310S6016 |
| C606 | CERAMIC CAP. 820pF/2kV | CA3D821PAN04 |
| C607 | CHIP CERAMIC CAP. B K 1800pF/50V | CHD1JK30B182 |
| C608 | CHIP CERAMIC CAP.(1608) B K 0.022µF/50V | CHD1JK30B223 |
| C609 | CHIP CERAMIC CAP. B K 0.068µF/50V | CHD1JK30B683 |
| C610 | CHIP CERAMIC CAP.(1608) CH J 100pF/50V | CHD1JJ3CH101 |
| C614  | CAP METALLIZED FILM 0.22µF/275V/K | CTA224PKR001 |
| C616  | SAFTY CAP. 1000pF/250V KX | CA2E102MR101 |
| C617  | CAP CERAMIC 100pF/250V KX | CA2E101MR100 |
| C622 | CHIP CERAMIC CAP.(2125) B K 10µF/6.3V | CHE0KK30B106 |
| C623 | CHIP CERAMIC CAP.(1608) B K 4.7µF/6.3V | CHD0KK30B475 |
| C651 | CAP ELE 470µF/25V/M/85 | CED4710V8006 |
| C652 | CAP ELE 470µF/25V/M/85 | CED4710V8006 |
| C653 | CAP ELE 470µF/25V/M/85 | CED4710V8006 |
| C654 | CAP ELE 470µF/16V/M/85 | CEC4710V8006 |
| C655 | CAP ELE 470µF/16V/M/85 | CEC4710V8006 |
| C656 | CAP ELE 1µF/50V/M/85 | CEF1R00V8006 |
| C660 | CHIP CERAMIC CAP.(1608) B K 0.22µF/25V | CHD1EK30B224 |
| C663 | CAP ELE 100µF/10V/M/85 | CEB1010V8006 |
| C665 | CHIP CERAMIC CAP.(1608) B K 0.1µF/50V | CHD1JK30B104 |
| C666 | CHIP CERAMIC CAP.(1608) B K 0.22µF/25V | CHD1EK30B224 |
| C1001 | CAP ELE 470µF/25V/M/85 | CED4710V8006 |
| C1002 | CAP ELE 470µF/25V/M/85 | CED4710V8006 |
| C1003 | CHIP CERAMIC CAP.(1608) B K 1µF/25V | CHD1EK30B105 |
| C1004 | CHIP CERAMIC CAP.(1608) B K 1µF/25V | CHD1EK30B105 |
| C1006 | CAP ELE 47µF/100V/M/85 | CEH4700V8006 |
| C1007 | CAP ELE 47µF/100V/M/85 | CEH4700V8006 |
| C1009 | CHIP CERAMIC CAP.(3216) X7R K 1.0µF/100V | CA2A105MR080 |
| C1010 | CHIP CERAMIC CAP.(3216) X7R K 1.0µF/100V | CA2A105MR080 |
| C1011 | CHIP CERAMIC CAP.(3216) X7R K 1.0µF/100V | CA2A105MR080 |
| C1012 | CHIP CERAMIC CAP.(1608) B K 1µF/25V | CHD1EK30B105 |
| C1013 | CHIP CERAMIC CAP.(1608) B K 1000pF/50V | CHD1JK30B102 |
| C1015 | CHIP CERAMIC CAP.(1608) B K 0.047µF/25V | CHD1EK30B473 |
| C1016 | CHIP CERAMIC CAP. B K 2200pF/50V | CHD1JK30B222 |
| C1017 | CHIP CERAMIC CAP.(1608) B K 0.022µF/50V | CHD1JK30B223 |
| C1018 | CERAMIC CAP. B K 100pF/1kV | CCD3AKN0B101 |
| C1019 | CHIP CERAMIC CAP.(1608) B K 1µF/25V | CHD1EK30B105 |
| C1020 | CHIP CERAMIC CAP. B K 2200pF/50V | CHD1JK30B222 |

CONNECTORS

| | | |
|---|---|--------------|
| CN501 | FFC CONNECTOR IMSA-9615S-23A-PP-A | JC96J23ER007 |
| CN601  | CONNECTOR S2P3-VH (LF)(SN) | JCVHC02JG002 |
| CN1001 | PH CONNECTOR TOP 2P B2B-PH-K-S (LF)(SN) | J3PHC02JG029 |

DIODES

| | | |
|---|-----------------------------------|--------------|
| D601 | DIODE 1N5406BH | NDL1001N5406 |
| D602 | DIODE 1N5406BH | NDL1001N5406 |
| D603 | DIODE 1N5406BH | NDL1001N5406 |
| D604 | DIODE 1N5406BH | NDL1001N5406 |
| D605 | ZENER DIODE MM5Z4V3B | ND1BMM5Z4V3B |
| D607A  | ZENER DIODE SMD TFZVTR27B | QD1B00TFZV27 |
| D608  | DIODE ZENER 1ZB36BB | NDWZ0001ZB36 |
| D609A  | DIODE SCHOTTKY SMD RB520SM-30 T2R | QD1ZRB520SM3 |
| D610 | DIODE SWITCHING HSC119 TRF -E | QD1Z00HSC119 |
| D621 | DIODE SWITCHING HSC119 TRF -E | QD1Z00HSC119 |
| D623 | ZENER DIODE MM5Z30B | ND1B0MM5Z30B |
| D650 | DIODE SCHOTTKY SB3150BH | NDWZ00SB3150 |
| D651 | DIODE SCHOTTKY SB3150BH | NDWZ00SB3150 |
| D653 | DIODE SCHOTTKY SB3A0BH | NDWZ000SB3A0 |
| D654  | DIODE ZENER 1ZB20BB | NDWZ0001ZB20 |
| D655 | DIODE SCHOTTKY SB3A0BH | NDWZ000SB3A0 |


| Ref. No. | Description | Part No. |
|--------------------|---|--------------|
| D656 | DIODE FAST RECOVERY RS1BJTD | ND1Z0RS1BJTD |
| D657 | ZENER DIODE MM5Z11B | ND1B0MM5Z11B |
| D660 | IC SHUNT REGULATOR SL431A-AT | NSZBA0TAUK01 |
| D661 | DIODE SWITCHING HSC119 TRF -E | QD1Z00HSC119 |
| D662 | IC SHUNT REGULATOR SL431A-AT | NSZBA0TAUK01 |
| D664 | ZENER DIODE SMD TFZVTR4.7B | QD1B0TFZV4R7 |
| D1001 | DIODE SCHOTTKY SMD SK210TD | ND1Z0SK210TD |
| D1004 | DIODE SWITCHING HSC119 TRF -E | QD1Z00HSC119 |
| D1005 | DIODE SWITCHING HSC119 TRF -E | QD1Z00HSC119 |
| D1006 | ZENER DIODE SMD TFZVTR30B | QD1B00TFZV30 |
| D1007 | ZENER DIODE MM5Z11B | ND1B0MM5Z11B |
| ICS | | |
| IC602▲ | IC PHOTOCOUPLER TLP781F(D4-FUNBLL F) | QPEL781FBLLF |
| IC1001 | IC LED BACKLIGHT CONTROLLER BD9488F-GE2/SOP/18P | QSCA0T0RM418 |
| COILS | | |
| L601▲ | COIL LINE FILTER JLB20154/18MH | LLEG0Z0XB022 |
| L602▲ | COIL LINE FILTER JLB20154/18MH | LLEG0Z0XB022 |
| L1001 | COIL POWER INDUCTORS DIP RP1315BNP-101M/100μH | LLF1010SF013 |
| TRANSISTORS | | |
| Q601▲ | FET MOS TK7P60W.RVQ(S | QF2Z0TK7P60W |
| Q602▲ | NPN TRANSISTOR SMD 2SC5344SY | NQZY2SC5344S |
| Q621 | CHIP TRANSISTOR KTC3875S-YRTK/P | NQ1YKTC3875S |
| Q650 | CHIP TRANSISTOR KTC3875S-YRTK/P | NQ1YKTC3875S |
| Q653 | CHIP TRANSISTOR KTC3875S-YRTK/P | NQ1YKTC3875S |
| Q656 | CHIP TRANSISTOR KTC3875S-YRTK/P | NQ1YKTC3875S |
| Q658 | TRANSISTOR 2SA950-O (TE2 F T) | QQS002SA950F |
| Q1001 | FET MOS SMD AP18T10AGH-HF | NF2Z18T10AGH |
| Q1003 | FET MOS SMD AP18T10AGH-HF | NF2Z18T10AGH |
| RESISTORS | | |
| R601▲ | RES. CARBON FILM J 1/2W J 1.2M Ω | RCX2125T1003 |
| R603 | RES CHIP 3216 1/4W J 470k Ω | RRX4474HH034 |
| R604 | RES CHIP 3216 1/4W J 470k Ω | RRX4474HH034 |
| R606 | RES CHIP 3216 1/4W J 330 Ω | RRX4331HH034 |
| R607 | RES CHIP 3216 1/4W J 330 Ω | RRX4331HH034 |
| R608 | RES CHIP 3216 1/4W J 1.5k Ω | RRX4152HH034 |
| R609 | RES CHIP 1608 1/10W J 100 Ω | RRXA101HH013 |
| R611▲ | METAL OXIDE RES. 2W J 0.36 Ω | RN02R36ZU001 |
| R612 | RES CHIP 3216 1/4W J 5.6k Ω | RRX4562HH034 |
| R613 | RES CHIP 3216 1/4W J 180 Ω | RRX4181HH034 |
| R614 | RES CHIP 3216 1/4W J 470k Ω | RRX4474HH034 |
| R621 | RES CHIP 1608 1/10W J 560 Ω | RRXA561HH013 |
| R622 | RES CHIP 1608 1/10W 0 Ω | RRXA000HH014 |
| R623 | RES CHIP 1608 1/10W J 10k Ω | RRXA103HH013 |
| R651▲ | RES CHIP 1608 1/10W J 1.0 Ω | RRXA1R0HH013 |
| R652 | RES CHIP 1608 1/10W F 56.0k Ω | RTW5602HH008 |
| R653 | RES CHIP 1608 1/10W F 33.0k Ω | RTW3302HH008 |
| R654 | RES CHIP 3216 1/4W J 180 Ω | RRX4181HH034 |
| R655 | RES CHIP 3216 1/4W J 180 Ω | RRX4181HH034 |
| R657 | RES CHIP 3216 1/4W J 3.9k Ω | RRX4392HH034 |
| R658 | RES CHIP 1608 1/10W J 2.7k Ω | RRXA272HH013 |
| R659 | RES CHIP 1608 1/10W F 27.0k Ω | RTW2702HH008 |
| R660 | RES CHIP 1608 1/10W F 3.90k Ω | RTW3901HH008 |
| R661 | RES CHIP 1608 1/10W F 3.30k Ω | RTW3301HH008 |
| R662 | RES CHIP 1608 1/10W F 3.30k Ω | RTW3301HH008 |
| R666 | RES CHIP 1608 1/10W 0 Ω | RRXA000HH014 |
| R667 | RES CHIP 1608 1/10W J 8.2k Ω | RRXA822HH013 |
| R668 | RES CHIP 1608 1/10W J 47k Ω | RRXA473HH013 |
| R669 | RES CHIP 1608 1/10W J 10k Ω | RRXA103HH013 |
| R670 | RES CHIP 1608 1/10W J 270 Ω | RRXA271HH013 |
| R671 | RES CHIP 1608 1/10W J 270 Ω | RRXA271HH013 |
| R672 | RES CHIP 1608 1/10W J 270 Ω | RRXA271HH013 |

| Ref. No. | Description | Part No. |
|----------------------|--------------------------------|--------------|
| R674 | RES CHIP 1608 1/10W 0 Ω | RRXA000HH014 |
| R675 | RES CHIP 1608 1/10W F 68.0k Ω | RTW6802HH008 |
| R677 | RES CHIP 1608 1/10W J 10k Ω | RRXA103HH013 |
| R680 | RES CHIP 1608 1/10W J 100 Ω | RRXA101HH013 |
| R681 | RES CHIP 1608 1/10W F 10.0k Ω | RTW1002HH008 |
| R682 | RES CHIP 1608 1/10W 0 Ω | RRXA000HH014 |
| R690▲ | RES CHIP 1608 1/10W J 1.5 Ω | RRXA1R5HH013 |
| R1001 | RES CHIP 1608 1/10W J 470 Ω | RRXA471HH013 |
| R1003 | RES CHIP 1608 1/10W J 1.0k Ω | RRXA102HH013 |
| R1004 | RES CHIP 1608 1/10W J 10k Ω | RRXA103HH013 |
| R1005 | RES CHIP 1608 1/10W J 100k Ω | RRXA104HH013 |
| R1006 | RES CHIP 1608 1/10W J 10k Ω | RRXA103HH013 |
| R1007 | RES CHIP 1608 1/10W J 100k Ω | RRXA104HH013 |
| R1009 | RES CHIP 3216 1/4W F 1.00 Ω | RT1R00RYL007 |
| R1010 | RES CHIP 3216 1/4W F 1.00 Ω | RT1R00RYL007 |
| R1011 | RES CHIP 1608 1/10W F 33.0k Ω | RTW3302HH008 |
| R1012 | RES CHIP 1608 1/10W F 56.0k Ω | RTW5602HH008 |
| R1013 | RES CHIP 1608 1/10W F 240k Ω | RTW2403HH008 |
| R1014 | RES CHIP 1608 1/10W F 3.00k Ω | RTW3001HH008 |
| R1015 | METAL OXIDE RES. 1W J 0.18 Ω | RN01R18ZU001 |
| R1019 | RES CHIP 1608 1/10W J 200 Ω | RRXA201HH013 |
| R1020 | RES CHIP 1608 1/10W F 240k Ω | RTW2403HH008 |
| R1021 | RES CHIP 1608 1/10W 0 Ω | RRXA000HH014 |
| R1022 | RES CHIP 1608 1/10W F 10.0k Ω | RTW1002HH008 |
| R1023 | RES CHIP 3216 1/4W J 3.9k Ω | RRX4392HH034 |
| R1024 | RES CHIP 3216 1/4W J 1.5k Ω | RRX4152HH034 |
| R1025 | RES CHIP 1608 1/10W J 1.0k Ω | RRXA102HH013 |
| R1026 | RES CHIP 1608 1/10W J 51 Ω | RRXA510HH013 |
| R1027 | RES CHIP 1608 1/10W F 22.0k Ω | RTW2202HH008 |
| R1028 | RES CHIP 1608 1/10W F 9.10k Ω | RTW9101HH008 |
| R1029 | RES CHIP 1608 1/10W F 9.10k Ω | RTW9101HH008 |
| R1030 | RES CHIP 1608 1/10W J 1.0k Ω | RRXA102HH013 |
| R1031 | RES CHIP 1608 1/10W J 10 Ω | RRXA100HH013 |
| MISCELLANEOUS | | |
| BC601 | BEADS INDUCTOR FBR07HA121SB-00 | LLBF00STU030 |
| BC602 | BEADS INDUCTOR FBR07HA121SB-00 | LLBF00STU030 |
| BC603 | BEADS INDUCTOR FBR07HA121SB-00 | LLBF00STU030 |
| BC604 | BEADS INDUCTOR FBR07HA121SB-00 | LLBF00STU030 |
| F602▲ | FUSE TIME RAG SLT250V2.5A | PDGSLB0NG252 |
| GP001 | EARTH PLATE A31FBUT | 1EM440258 |
| GP002 | EARTH PLATE A31FBUT | 1EM440258 |
| GP003 | EARTH PLATE A31FBUT | 1EM440258 |
| JS603 | WIRE CP STP-S-0.50 | XZ40F0REN001 |
| JS604 | WIRE CP STP-S-0.50 | XZ40F0REN001 |
| SA601▲ | VARISTOR 10D 471K SVR | NVQZVR10D471 |
| T601▲ | TRANS POWER SRW26LEC-T11H016 | LTT2PC0TE005 |

TYPE A


PARTS LIST [32PFL3508/F8 (Serial No.: XA2)]

Mechanical Parts


PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTE: Parts that are not assigned part numbers (-----) are not available.

Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|--|---|--------------|
| LCD1  | LCD PANEL ASSEMBLY | U3DF0PA |
| CL3006 | FFC WIRE ASSEMBLY 30PIN(W/SHIELD) 30P/ FFC/SHIELD/415MM | WX1A3AFBP401 |
| L23 | SCREW S-TIGHT M3X6 BIND HEAD+ | GBJS3060 |
| W02 | WIRE ASSEMBLY 50PIN FFC SF250-0080XWY00 | WX1U3DF0-F01 |

Electrical Parts

PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTES:

1. Parts that are not assigned part numbers (-----) are not available.
2. Tolerance of Capacitors and Resistors are noted with the following symbols.

C.....±0.25% D.....±0.5% F.....±1%
G.....±2% J.....±5% K.....±10%
M.....±20% N.....±30% Z.....+80/-20%


Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|----------|---------------------------|--------------|
| | DIGITAL MAIN CBA UNIT | A3AFLMMA-001 |
| | POWER SUPPLY CBA | A3AFBMPW-001 |
| R1015 | METALOXIDE RES 2W J 0.12Ω | RNJR12PAK002 |

TYPE A



PARTS LIST [32PFL3508/F7 (Serial No.: ME1)]

Mechanical Parts


PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTE: Parts that are not assigned part numbers (-----) are not available.

Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|---|-------------------------------------|------------|
| A15  | RATING LABEL A3AF2UT | ----- |
| A16 | LOGO LABEL A3AF2UT | ----- |
| A17 | ENERGY GUIDE LABEL A3AF2UT | ----- |
| S1 | CARTON A3AF2UT | 2EMC00230 |
| S12 | Not used | |
| X2  | OWNERS MANUAL A31M2UT | 2EMN00083A |
| X6 | QUICK START GUIDE A3AF2UT | 2EMN00111 |
| X7 | REGISTRATION CARD (PHILIPS) A2176UT | 1EMN29339 |

Electrical Parts

PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTES:

1. Parts that are not assigned part numbers (-----) are not available.
2. Tolerance of Capacitors and Resistors are noted with the following symbols.

| | | |
|--------------|-------------|----------------|
| C.....±0.25% | D.....±0.5% | F.....±1% |
| G.....±2% | J.....±5% | K.....±10% |
| M.....±20% | N.....±30% | Z.....+80/-20% |


Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|----------|-----------------------|--------------|
| | DIGITAL MAIN CBA UNIT | A3AF2MMA-002 |

TYPE A



PARTS LIST [32PFL1508/F8 (Serial No.: XA1)]

Mechanical Parts


PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTE: Parts that are not assigned part numbers (-----) are not available.

Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|--|--|--------------|
| A15  | RATING LABEL A3AFRMA | ----- |
| A16 | LOGO LABEL A3AQZUH | ----- |
| S1 | CARTON A3AFRMA | 2EMC00204 |
| S12 | CARTON LABEL A3AFRMA | ----- |
| LCD1  | LCD PANEL ASSEMBLY | U3DF0PB |
| A1 | FRONT CABINET A3AFRMA | 2EMM00211 |
| A5 | Not used | |
| A6 | CONTROL PLATE A31F0UT | 1EM334317 |
| A9 | SENSOR LENS A3AF0UT | 1EM334258 |
| B12 | SHIELD PLATE A3AF0UT | 1EM334260 |
| CL3006 | FFC WIRE ASSEMBLY 30PIN(W/SHIELD) 30P/ FFC/SHIELD/415MM | WX1A3AFBP401 |
| L23 | SCREW S-TIGHT M3X6 BIND HEAD+ | GBJS3060 |
| W02 | WIRE ASSEMBLY 50PIN FFC SF250- 0080XWY00 | WX1U3DF0-F01 |

Electrical Parts

PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTES:

1. Parts that are not assigned part numbers (-----) are not available.
2. Tolerance of Capacitors and Resistors are noted with the following symbols.

C.....±0.25% D.....±0.5% F.....±1%
G.....±2% J.....±5% K.....±10%
M.....±20% N.....±30% Z.....+80/-20%


Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|----------|---------------------------|--------------|
| | DIGITAL MAIN CBA UNIT | A3AFRMA-001 |
| | | |
| | POWER SUPPLY CBA | A3AFBMPW-001 |
| R1015 | METALOXIDE RES 2W J 0.12Ω | RNJR12PAK002 |

TYPE B



PARTS LIST [32PFL1508/F8 (Serial No.: DS1)]

Mechanical Parts


PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTE: Parts that are not assigned part numbers (-----) are not available.

Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|--|--|--------------|
| A4 | BOTTOM COVER A3AFCUH | 1EM031005 |
| A15  | RATING LABEL A3AFVMH | ----- |
| A16 | LOGO LABEL A3AQZUH | ----- |
| SA1 | STAND ASSEMBLY A21F0UH | 1EM029048A |
| SSK1 | STAND SCREW KIT A3AFCUH(SCREW P-TIGHT M4X14 BIND HEAD+BLK) | 1ESA35205 |
| S1 | CARTON A3AFVMH | 2EMC00248 |
| S6 | SET BAG A21F0UH | 1EM335137 |
| S12 | CARTON LABEL A3AFVMH | ----- |
| X2  | OWNERS MANUAL A3ATAMA | 2EMN00033A |
| X6 | QUICK START GUIDE A3ATAMA | 2EMN00034A |
| LCD1  | LCD PANEL ASSEMBLY | U34F7P0 |
| A1 | FRONT CABINET A3AFVMH | 2EMM00224 |
| A5 | Not used | |
| A6 | CONTROL PLATE A31F0UT | 1EM334317 |
| A9 | SENSOR LENS A3AF0UT | 1EM334258 |
| B12 | SHIELD PLATE A3AF0UT | 1EM334260 |
| CL3006 | FFC WIRE ASSEMBLY 30PIN(W/SHIELD) 30P/FFC/SHIELD/600MM | WX1A3AFCP411 |

Electrical Parts

PRODUCT SAFETY NOTE: Products marked with a  have special characteristics important to safety. Before replacing any of these components, read carefully the product safety notice in this service manual. Don't degrade the safety of the product through improper servicing.

NOTES:

1. Parts that are not assigned part numbers (-----) are not available.
2. Tolerance of Capacitors and Resistors are noted with the following symbols.

C.....±0.25% D.....±0.5% F.....±1%
G.....±2% J.....±5% K.....±10%
M.....±20% N.....±30% Z.....+80/-20%

Different parts from the original model 32PFL3508/F8 (Serial No. : XA1)

| Ref. No. | Description | Part No. |
|----------|---|--------------|
| | DIGITAL MAIN CBA UNIT | A3AFVMA-001 |
| IC3006 | 32MBIT C-MOS SERIAL FLASH F25L32QA-100PAG2S | NSCA0R0E1019 |
| IC3621 | Not used | |
| TU3901 | TUNER UNIT U9001UH | U9001UH |
| | | |
| | FUNCTION CBA UNIT | A3AFVMSW-001 |
| | | |
| | POWER SUPPLY CBA | A3AFNMPW-001 |
| R1014 | RES CHIP 1608 1/10W F 5.60k Ω | RTW5601HH008 |
| R1015 | RES METAL OXIDE 1W J 0.12 Ω | RNJR120HH013 |

REVISION HISTORY

Chassis PL13.8

- 2013/6/18 32PFL3508/F8 (Serial No.: XA1) Added
- 2013/7/9 32PFL3508/F8 (Serial No.: XA2) Added
- 2013/8/22 32PFL1508/F8 (Serial No.: XA1) Added
- 2013/8/22 32PFL1508/F8 (Serial No.: DS1) Added
- 2013/9/26 32PFL3508/F7 (Serial No.: ME1) 1st draft added

COMPARISON LIST OF MODEL NAMES

Chassis PL13.8

| | | | |
|--------------|-------|---------|--------|
| 32PFL3508/F7 | (ME1) | A3AF2UT | TYPE A |
| 32PFL3508/F8 | (XA1) | A3AFEMA | TYPE A |
| | (XA2) | A3AFLMA | TYPE A |
| 32PFL1508/F8 | (XA1) | A3AFRMA | TYPE A |
| | (DS1) | A3AFVMH | TYPE B |